



PLT13 REWIRABLE PLUG

ELECTRICAL

Rated Voltage	250V a.c.
Rated Current	13Amp
Frequency	50Hz / 60Hz
Fused	13Amp fuse 3Amp fuse (for C5 and C7 cordsets)
Terminal capacity: Live, Neutral & Earth	1.5 mm ² (3 Core cable)

ENVIRONMENTAL

Ambient Operating Temperature	-5°C to +40°C (not to exceed an average of more than 25°C in any 24 hours period)
Degree of Protection	Ordinary

MATERIAL

Material (Enclosure)	Polycarbonate
Metal Components Material	Brass, Phosphor Bronze
Weight	Estimated 75 grams
Compliance	BS 5733:1995 / SS 241:1996 PSB test mark DIN VDE 0620-1
Guarantee	3 years subject to Eubiq Limited Warranty Statement



www.eubiq.com

EUBIQ PRIVATE LIMITED. 9 JOO KOON CRESCENT SINGAPORE 629025
ALL RIGHTS RESERVED. EUBIQ AND GSS ARE REGISTERED TRADEMARKS OF EUBIQ PTE LTD.

DISCLAIMER: EUBIQ PRIVATE LIMITED RESERVES THE RIGHT TO ALTER ANY DETAILS OF SPECIFICATIONS OR EQUIPMENT WITHOUT PRIOR NOTICE. DETAILS OF SPECIFICATIONS AND EQUIPMENT ARE ALSO SUBJECT TO CHANGES TO SUIT LOCAL STANDARDS, CONDITIONS AND REQUIREMENTS. PLEASE CONSULT YOUR LOCAL DEALER FOR MORE INFORMATION OR LOGON TO EUBIQ WEBSITE.