


PLT16 REWIRABLE PLUG

User Guide


Technical Specifications

Product Description	: Rewirable Plug
Rated Voltage	: 250 V a.c.
Rated Current	: 16 Amp
Frequency	: 50Hz/60Hz
Fused	: Fused Link
Terminal Capacity (Live, Neutral and Earth)	: 1.5mm ² (3 Core cable)
Ambient Operating Temp.	: -5°C to +40°C (Not to exceed an average of more than 25°C in any 24 hours period)
Degree of Protection	: Ordinary
Material (Enclosure)	: Polycarbonate
Metal Components Material	: Brass, Phosphors Bronze
Weight	: Estimated 75 grams


⚠ PLEASE READ BEFORE USE



Do not drag adaptor along the track.






Do not leave adaptor "ON" when not in use.



Do not insert adaptor without aligning Locator to V-Groove.



- Keep away from fire.
- Keep away from water.
- Not for outdoor use.
- To be installed by a qualified electrician/installer.

User Instructions



Wiring Instruction

Prepare leads as shown:



- Live (Brown or Red)
- Earth (Green or Green/Yellow)
- Neutral (Blue or Black)

3 Years Limited Warranty

- Eubiq Pte Ltd ("Eubiq") warrants to the end-user of the ("the Customer") that the product will be free from defects in materials and workmanship under normal use for a period of three (3) years from the date of retail purchase by the original end-user purchaser ("Warranty Period").
- The Customer should access and refer to Eubiq's website at www.eubiq.com for a list of Eubiq authorised dealers to contact for warranty service.
- All requests for warranty service must be made within the Warranty Period, and be accompanied by the original dated proof of purchase.

www.eubiq.com